



Model Name	AN-328PC
Ballast Type	Electronic
Starting Method	Modified Rapid Start
Lamp connection	Series
Input Voltage	347 Vac
Input Frequency	50/60 Hz
Warranty	3 Years 0°C ≤ Temp. ≤ 50°C

Safety & Performance




- One lamps
- Sound Rated Class A
- Auto Restart
- UL/cUL Listed
- Class P Thermally Protected
- No PCBs
- UL Type 1 Outdoor
- Normal Power Factor
- Single 28W 2D lamp
- FCC part 18 Class A
- Surge Protected
- Open circuit voltage:450V

Electrical Specification with Different Lamps

Lamp Type	No. of Lamps	Input Voltage (V)	Rated Lamp Watts	Start Temp Min. (F/C)	Input Current (Amps)	Input Power (ANSI Watts)	Ballast Factor	Power Factor	Lamp Current Crest Factor Max.	BEF
2D 28	1	347	28	32/0	0.19	27	0.67	0.45	1.7	2.48


Wire Diagram



Lead Length	Inch	Cm
Black	14.5	36.8
White	14.5	36.8

Maximum Wiring Distance (at full load) is 18AWG/18Feet

Enclosure



AP16

Enclosure	Inch	Cm
A	1.46	3.7
B	3.82	9.7
C	3.125	7.9
D	4.33	11
E	2.375	6
Mount on Center	3.88	9.9