




Model Name	ESS-A54T5S
Ballast Type	Electronic
Starting Method	Program Start
Lamp connection	Series
Input Voltage	120-277V
Input Frequency	50/60Hz
Warranty	5 Years $TC \leq 75^{\circ}C$ 3 Years $75^{\circ}C \leq TC \leq 90^{\circ}C$

Safety & Performance




- One lamp
- UL/cUL Listed
- UL Type 1 Outdoor
- FCC part 18 Class A
- Sound Rated Class A
- Class P Thermally Protected
- High Power Factor
- Surge Protected
- Auto Restart
- No PCBs
- Type HL
- DOE Energy Verified

Wire Diagram



Maximum Wiring Distance (at full load) is 18AWG/18Feet
Case must be grounded

Enclosure



AM34

Enclosure	Inch	Cm
Length(L)	11.5	29.2
Width(W)	1.34	3.4
Height(H)	1.06	2.7
Mounting(M)	11.14	28.3



Electrical Specification with Different Lamps

Lamp Type	No. of Lamps	Input Voltage (V)	Rated Lamp Watts	Start Temp Min. (F/C)	Input Current (Amps)	Input Power (ANSI Watts)	Ballast Factor	THD Max. (%)	Power Factor	Lamp Current Crest Factor Max.	BEF
54W T5	1	120	54	-22/-30	0.45	55	0.85	10	0.99	1.7	1.55
		230			0.23			10	0.99		
		277			0.2			10	0.98		
55W PLL	1	120	55	-22/-30	0.4	49	0.75	10	0.99	1.7	1.56
		230			0.2			10	0.99		
		277			0.18			15	0.98		
50W PLL	1	120	50	-22/-30	0.46	56	0.91	10	0.99	1.7	1.65
		230			0.23			10	0.99		
		277			0.2			10	0.98		
39W T5HO	1	120	39	-22/-30	0.35	43	0.85	10	0.99	1.7	2.13
		230			0.17			15	0.98		
		277			0.14			15	0.97		