



Antron Electronics Co.,LTD
安雄電子股份有限公司

T5 Modified Rapid Start Ballast



Model Name	CSS-724T5NPF
Ballast Type	Electronic
Starting Method	Modified Rapid Start
Lamp connection	Series
Input Voltage	277V
Input Frequency	50/60Hz
Warranty	5 Years $TC \leq 75^{\circ}C$ 3 Years $75^{\circ}C \leq TC \leq 90^{\circ}C$

Safety & Performance




- One lamp
- UL/cUL Listed
- UL Type 1 Outdoor
- FCC part 18 Class A
- Sound Rated Class A
- Class P Thermally Protected
- Normal Power Factor
- Surge Protected
- Auto Restart
- No PCBs
- Type HL

Electrical Specification with Different Lamps

Lamp Type	No. of Lamps	Input Voltage (V)	Rated Lamp Watts	Start Temp Min. (F/C)	Input Current (Amps)	Input Power (ANSI Watts)	Ballast Factor	Power Factor	Lamp Current Crest Factor Max.	BEF
24W T5	1	277	24	32/0	0.2	28	0.88	0.4	1.7	3.14


Wire Diagram



Lead Length	Inch	Cm
Black	11.81	30
White	11.81	30
Blue	13.78	35
Red	13.78	35

Maximum Wiring Distance (at full load) is 18AWG/18Feet
Case must be grounded

Enclosure



AM39

Enclosure	Inch	Cm
Length(L)	3.9	9.9
Width(W)	2.05	5.2
Height(H)	1.18	3.0
Mounting(M)	3.58	9.1

Published 2013/10/8

Revised 2020/4/28